International Journal of Computer Engineering and Technology (IJCET)
Volume 16, Issue 1, Jan-Feb 2025, pp. 3316-3330, Article ID: IJCET_16_01_231
Available online at https://iaeme.com/Home/issue/IJCET?Volume=16&Issue=1
ISSN Print: 0976-6367; ISSN Online: 0976-6375; Journal ID: 5751-5249
Impact Factor (2025): 18.59 (Based on Google Scholar Citation)
DOI: https://doi.org/10.34218/IJCET_16_01_231

TRUST-BUILDING THROUGH SHARED CONTROL: HUMAN-IN-THE-LOOP ADAS

Vraj Mukeshbhai Patel
May Mobility Inc, USA.

ABSTRACT

The importance of human-in-the-loop techniques in advanced driver assistance systems (ADAS) for establishing and preserving driver trust is examined in this article. It provides a thorough examination of shared control paradigms in fully autonomous and semi-autonomous cars, emphasizing how carefully incorporating human oversight improves user confidence and system dependability. It examines adaptive cruise control and lane-keeping assistance implementations to show how well-balanced human-machine partnerships reduce driver fatigue while maintaining safety. It delves deeper *into remote assistance protocols and teleoperation frameworks, demonstrating how well they manage edge cases and environmental difficulties. According to this article, ongoing feedback loops between AI systems and human operators enhance algorithmic performance and foster enduring confidence in autonomous car technologies. This article adds to the expanding collection of works on human-centered design.*

Keywords: Human-in-the-loop ADAS, Shared vehicle control, Trust-building automation, Teleoperation systems, Autonomous vehicle safety.

Cite this Article: Vraj Mukeshbhai Patel. Trust-Building Through Shared Control: Human-in-the-Loop ADAS. *International Journal of Computer Engineering and Technology (IJCET)*, 16(1), 2025, 3316-3330.

https://iaeme.com/MasterAdmin/Journal_uploads/IJCET/VOLUME_16_ISSUE_1/IJCET_16_01_231.pdf

1. Introduction: The Trust Challenge in Vehicle Automation

1.1 Current Landscape of Vehicle Automation

The automotive industry is experiencing a transformative shift as advanced driver assistance systems (ADAS) fundamentally alter the dynamics between humans and vehicles. A study (2020) [1] found that 54% of drivers express interest in autonomous features, only 23% have full confidence in current ADAS implementations. This stark contrast in adoption versus trust metrics presents a critical challenge for manufacturers and system designers. The study further reveals that drivers aged 25-34 show the highest acceptance rate at 62%, while those over 55 demonstrate only 31% acceptance, highlighting a significant generational divide in ADAS adoption patterns [1].

1.2 The Evolution of Trust Mechanisms

The progression of ADAS capabilities has introduced increasingly sophisticated features, ranging from foundational cruise control systems to advanced lane-keeping assistance and autonomous parking mechanisms. However, the path to widespread acceptance has been complex. Research indicates that drivers who receive proper training and understanding of their vehicle's assistance features demonstrate a 45% higher engagement rate with ADAS technologies, leading to a significant 33% reduction in cognitive load during demanding driving scenarios [2]. This correlation between understanding and utilization emphasizes the crucial role of user education in building trust.

Trust-building mechanisms in autonomous vehicles extend beyond mere technological capability. Integrating human-centric design principles has shown that systems providing clear feedback and predictable behavior patterns achieve 40% higher user satisfaction rates [1]. Additionally, vehicles equipped with intuitive human-machine interfaces (HMI) demonstrate a 28% increase in feature utilization across all age groups, suggesting that accessibility and user experience play pivotal roles in trust development [2].

1.3 Human-in-the-Loop Framework Evolution

Human-in-the-loop (HITL) approaches represent a sophisticated solution to address the trust deficit in autonomous systems. By intentionally incorporating human judgment within the autonomous decision-making framework, HITL creates a dynamic partnership between driver and vehicle. Studies indicate that systems implementing HITL frameworks show a 37% improvement in user trust metrics compared to fully autonomous alternatives [2]. This enhancement in trust correlates with a 25% increase in system effectiveness, particularly in complex driving scenarios [1].

It explores how shared control serves as a fundamental trust-building mechanism, examining both technological and psychological aspects of human-machine interaction. Research demonstrates that drivers interacting with shared control systems report a 42% higher sense of confidence in their vehicle's capabilities [2]. This increased confidence translates to more effective use of autonomous features, creating a positive feedback loop that further enhances system reliability.

Real-world implementation data reveals that vehicles incorporating HITL approaches experience a 31% reduction in override events and a 29% improvement in system prediction accuracy [1]. These metrics suggest that the synergy between human insight and machine precision not only enhances safety but also cultivates a deeper sense of trust in autonomous technology.

2. Foundations of Shared Control Systems

2.1 Adaptive Decentralized Sensor Architecture

The foundation of modern ADAS relies on a sophisticated decentralized sensor fusion architecture that revolutionizes how vehicles perceive and interact with their environment. According to recent research, the decentralized approach processes sensor data through distributed nodes, achieving a remarkable 76% reduction in communication bandwidth compared to centralized architectures [3]. This system employs adaptive Kalman filtering techniques that adjust in real-time based on sensor reliability metrics, maintaining an average position estimation error of less than 0.3 meters even in challenging environmental conditions. The architecture demonstrates exceptional robustness, with sensor nodes operating independently at frequencies between 10 Hz and 50 Hz while maintaining system coherence through sophisticated time synchronization protocols [3].

2.2 Multi-Modal Perception Integration

The integration of multiple sensor modalities forms the cornerstone of reliable shared control systems. Research indicates that the fusion of radar, LiDAR, and camera data through adaptive weighting mechanisms achieves a positioning accuracy of 0.15 meters in optimal conditions and maintains accuracy within 0.5 meters in adverse weather [4]. The system's perception framework incorporates advanced state estimation algorithms that handle sensor uncertainties with a confidence level of 95%, particularly crucial for maintaining consistent tracking of surrounding vehicles at varying speeds and distances [3]. This multi-modal approach has demonstrated significant improvements in object detection and classification, with false positive rates reduced to 0.8% in complex urban environments.

2.3 Dynamic Control Authority Management

The implementation of dynamic control authority represents a critical advancement in shared control systems. Studies show that adaptive control allocation algorithms can predict driver intentions with 89% accuracy within a 300-millisecond window [4]. The system continuously adjusts control authority distribution based on real-time risk assessment, maintaining a safety envelope that adapts to both driver behavior and environmental conditions. Research demonstrates that this approach reduces control conflicts by 67% compared to static authority allocation methods [3].

2.4 Real-Time Performance Optimization

Performance optimization in shared control systems involves continuous adaptation to changing conditions while maintaining strict safety constraints. The adaptive fusion framework demonstrates remarkable resilience, maintaining tracking accuracy even when up to 30% of sensors experience degraded performance [3]. This robustness is achieved through sophisticated fault detection algorithms that can identify and compensate for sensor failures within 50 milliseconds, ensuring uninterrupted system operation [4].

The system's real-time optimization capabilities extend to computational resource management, with dynamic load balancing achieving a 45% reduction in processing latency compared to static allocation approaches. State estimation accuracy remains within 0.2 meters for relative positioning tasks, even under high-speed scenarios reaching 120 km/h [3]. Furthermore, the integration of predictive control algorithms has shown a 78% improvement in trajectory planning accuracy, with path prediction errors remaining below 0.4 meters for a 3-second prediction horizon [4].

2.5 Safety Assurance Framework

The safety assurance framework incorporates multiple layers of redundancy and validation, with each layer operating independently to ensure system reliability. Testing has shown that the decentralized architecture maintains full functionality even with a 40% sensor degradation rate, demonstrating superior resilience compared to centralized approaches [3]. The system's adaptive nature allows it to maintain a 92% detection rate for critical scenarios while operating within a computational budget of 100 milliseconds per control cycle [4].

Table 1: Comparative Analysis of Sensor Fusion Accuracy in Autonomous Vehicles [3, 4]

Environmental Condition	Positioning Accuracy (meters)	Detection Rate (%)	Sensor Latency (ms)
Optimal Weather	0.15	95	50
Light Rain	0.25	92	65
Heavy Rain	0.50	85	85
Night Time	0.35	88	70
Dense Traffic	0.30	90	60
Urban Canyons	0.45	87	75

3. Semi-Autonomous Implementation

3.1 Advanced Driver Assistance Architecture

Semi-autonomous systems represent a significant advancement in vehicular control, integrating sophisticated monitoring and decision-making mechanisms. Research indicates that modern ADAS platforms reduce driver cognitive load by up to 35% during extended highway driving while maintaining a 95% detection rate for safety-critical events [5]. The architecture implements a hierarchical control structure where safety-critical functions operate at high frequencies (100Hz) while strategic planning modules run at lower frequencies (10-20Hz), creating a balanced framework for system responsiveness [6]. Studies show that this multi-layered approach has resulted in a 47% reduction in driver intervention requirements during normal operation conditions.

3.2 Integrated Safety Systems

Contemporary ADAS implementations incorporate multiple safety subsystems working in harmony. Forward Collision Warning (FCW) systems demonstrate 92% accuracy in threat detection with a false alarm rate of less than 1.5% [5]. The integration of Lane Departure Warning (LDW) with corrective steering assistance has shown a 78% reduction in unintended lane departures. These systems maintain effectiveness even under challenging conditions, with performance degradation limited to 15% in adverse weather [6]. The combined effect of these safety systems has resulted in a documented 43% reduction in rear-end collisions and a 38% decrease in lane departure incidents.

3.3 Human-Machine Interface Optimization

The effectiveness of semi-autonomous systems heavily depends on the quality of human-machine interaction. Research demonstrates that optimized interface designs reduce driver response times by 28% during takeover requests [5]. The system incorporates:

Multi-modal warning systems achieve 89% driver compliance rates through synchronized visual, auditory, and haptic feedback channels. Adaptive warning thresholds, calibrated to individual driver patterns, show a 34% improvement in driver trust metrics [6]. Studies indicate that personalized feedback mechanisms reduce alarm fatigue by 52% while maintaining safety standards.

3.4 Performance Validation Framework

Comprehensive testing protocols validate system performance across diverse operational conditions. Real-world data collected over 1.2 million kilometers shows that enhanced ADAS systems maintain 94% reliability in urban environments and 97% on highways [5]. The validation framework incorporates continuous monitoring of key performance indicators:

System responsiveness maintains consistent performance with control loop delays under 85 milliseconds, meeting safety-critical timing requirements. Intervention accuracy shows 96% alignment with expert driver decisions in complex scenarios [6]. Long-term reliability metrics indicate mean time between failures (MTBF) exceeds 3,000 hours of operation.

3.5 Adaptive Control Implementation

The implementation of adaptive control strategies shows significant improvements in system performance. Research indicates that machine learning-enhanced control algorithms adapt to individual driving styles within 200 kilometers of operation, achieving an 87% match with driver preferences [5]. The system demonstrates remarkable flexibility in handling various driving conditions:

Speed control maintains accuracy within ±1.5 km/h of target values while reducing energy consumption by 12% compared to human drivers [6]. Lane positioning accuracy stays within 5 centimeters under normal conditions and 12 centimeters in adverse weather, representing a 65% improvement over previous generations.



	Highway Driving	Urban Environment	Heavy Traffic	Night Operations	Adverse Weather	Complex Junctions
Safety Incident Reduction (%)	43	38	41	35	32	36
System Accuracy (%)	97	94	93	85	82	89
Driver Workload Reduction (%)	35	28	31	33	25	22

Fig. 1: Comparative Analysis of ADAS Safety and Comfort Metrics [5, 6]

4. Teleoperation and Remote Assistance

4.1 Virtual Reality Integration in Remote Operations

Teleoperation systems have evolved significantly with the integration of virtual reality (VR) technology in remote monitoring and control operations. Research demonstrates that VR-enhanced teleoperation reduces operator response times by 42% compared to traditional 2D interfaces while improving spatial awareness by 67% [7]. The implementation of high-fidelity VR systems requires specialized infrastructure capable of maintaining stable frame rates of 90 fps with motion-to-photon latency under 20ms. Studies show that operators using VR interfaces maintain effective control even with network latencies up to 150 ms through predictive rendering techniques [8].

4.2 Operator Interaction Frameworks

The effectiveness of remote operation heavily depends on the operator's ability to maintain situational awareness and make timely decisions. Research indicates that operators using sequence-based control protocols achieve 89% success rates in complex urban scenarios, with average intervention times reduced to 2.3 seconds [8]. The interaction framework incorporates multiple levels of automation:

Direct Control Mode demonstrates 95% accuracy in precise maneuvering tasks when enhanced with haptic feedback systems [7]. Supervisory Control enables a single operator to monitor up to 8 vehicles simultaneously during standard operations, with automated systems handling routine tasks. Strategic Control allows operators to manage complex scenarios across multiple vehicles with a 78% reduction in cognitive load compared to traditional approaches [8].

4.3 Remote Operation Center Optimization

Modern remote operation facilities implement sophisticated monitoring and decision support systems. Analysis of operator performance shows that AI-assisted decision making improves intervention accuracy by 34% while reducing operator fatigue by 56% during extended sessions [7]. The centers maintain:

Continuous monitoring of vehicle telemetry with update rates of 60Hz for critical systems and 10Hz for environmental data. Automated anomaly detection achieves 92% accuracy in identifying potential issues before they become critical [8]. Performance metrics indicate that integrated predictive algorithms reduce unnecessary interventions by 45% while maintaining safety standards.

4.4 Risk Management and Safety Protocols

The implementation of comprehensive safety protocols is crucial for reliable teleoperation. Studies show that multi-layered safety systems achieve 99.97% detection rates for potential hazards, with automated response times averaging 300ms [7]. Safety frameworks incorporate:

Predictive risk assessment algorithms identify potential hazards up to 5 seconds in advance, providing operators with crucial decision-making time. Automated fallback systems maintain vehicle safety with 99.9% reliability when communication delays exceed acceptable thresholds [8]. Research indicates that these safety measures reduce incident rates by 82% compared to systems without comprehensive safety protocols.



Fig. 2: Comparative Analysis of VR vs Traditional Interface in Remote Vehicle Operation [7, 8]

5. Trust Development Through Machine Learning

5.1 Trust Calibration Through Artificial Intelligence

The development of trust in autonomous systems relies on advanced machine learning frameworks that continuously adapt to user interactions. Research indicates that AI-driven trust calibration systems achieve 82% accuracy in predicting user trust levels by analyzing behavioral patterns and interaction data [9]. The implementation of hierarchical neural networks enables the processing of multimodal trust indicators, with a demonstrated 71% improvement in trust assessment accuracy compared to traditional methods [10]. These systems incorporate real-time feedback loops that adapt to individual user preferences, showing a 43% reduction in trust calibration time compared to static approaches.

5.2 Dynamic Learning Integration

The continuous refinement of trust-building algorithms represents a critical aspect of autonomous system development. Studies show that adaptive learning models enhanced with explainable AI components demonstrate a 65% improvement in user understanding and acceptance [9]. The system achieves:

Trust development frameworks show 88% effectiveness in building appropriate trust levels, avoiding both overtrust and undertrust scenarios. Behavioral analysis algorithms maintain 94% accuracy in identifying critical trust breakdown points, enabling proactive intervention strategies [10]. Research indicates that integrated learning systems reduce trust-related incidents by 56% while maintaining optimal performance parameters.

5.3 Human-AI Collaboration Framework

The integration of human feedback in machine learning systems plays a crucial role in developing sustainable trust relationships. Analysis shows that structured human-AI collaboration frameworks improve system reliability by 37% while reducing user anxiety levels by 45% [9]. The system demonstrates:

Adaptive interaction patterns that maintain 91% alignment with user expectations during critical decision points. Natural language processing components achieve 86% accuracy in interpreting user intent and emotional state [10]. Implementation of these frameworks shows a 59% improvement in user confidence levels during the first month of interaction.

5.4 Trust Metrics and Validation

Comprehensive trust validation frameworks ensure consistent improvement in system-user relationships. Research analyzing over 1,000 human-AI interactions reveals:

Initial trust establishment periods were reduced by 40% through the implementation of transparent AI decision processes [9]. User confidence metrics show 77% improvement in understanding system capabilities and limitations. Long-term trust maintenance success rates of 84% across diverse user groups [10]. The validation framework incorporates continuous monitoring of key trust indicators:

- Neural response patterns during critical decisions
- Behavioral adaptation rates in varying scenarios
- User engagement levels during system interactions

5.5 Adaptive Trust Architecture

The architecture of trust-building systems involves sophisticated adaptation mechanisms that respond to individual user characteristics. Studies indicate that personalized trust development approaches achieve 79% higher retention rates in system usage [9]. The framework demonstrates:

Dynamic trust calibration achieves 89% accuracy in predicting user trust thresholds. Continuous learning mechanisms show a 0.7% weekly improvement in trust prediction accuracy [10]. Implementation results indicate a 52% reduction in trust-related system disengagements compared to static trust models.

6. Future Implications and Industry Impact

6.1 Global Industry Transformation

Recent research indicates that autonomous vehicle technology will reshape the automotive industry landscape significantly through 2030. Expert discussions predict that 40% of urban vehicles will have Level 3 or higher automation capabilities by 2027, with adoption rates varying significantly across different regions [11]. Analysis shows that Asian markets may lead initial adoption with a projected 45% market share, followed by North America at 35% and Europe at 30%. Research indicates that cities investing in smart infrastructure demonstrate 62% higher autonomous vehicle integration rates compared to those without such investments [12].

6.2 Regulatory Evolution and Safety Standards

The development of comprehensive regulatory frameworks represents a critical factor in autonomous vehicle adoption. Studies show that harmonized international standards could reduce certification costs by 35% while improving cross-border operability by 58% [12]. The regulatory landscape encompasses:

Current federal motor vehicle safety standards (FMVSS) adaptation shows 85% coverage of autonomous vehicle requirements, with key gaps identified in human-machine interface regulations [11]. Safety validation protocols demonstrate a 73% improvement in standardization across major markets. Research indicates that regulatory harmonization could accelerate market entry timelines by 40% while maintaining rigorous safety standards [12].

6.3 Societal Integration and Urban Planning

The integration of autonomous vehicles into urban environments presents both opportunities and challenges. Expert analysis reveals that smart city initiatives incorporating autonomous vehicle infrastructure could reduce urban congestion by 25% by 2030 [11]. Implementation considerations include:

Urban mobility patterns show potential for a 30% reduction in parking space requirements. Environmental impact assessments indicate a 28% decrease in emissions through optimized routing and reduced idling time [12]. Social acceptance metrics demonstrate a 15% annual improvement through community engagement and education programs.

6.4 Economic Impact Framework

Comprehensive economic analysis reveals significant implications for multiple sectors. Studies project:

Infrastructure investment requirements range from $23 billion to $48 billion over the next decade [11]. Insurance model transformations indicate a 40% reduction in traditional coverage costs. Employment impact shows 18% growth in specialized technical roles while traditional driving positions decline by 12% [12].

6.5 Future-Ready Implementation Strategy

The development of robust implementation strategies remains crucial for successful autonomous vehicle integration. Research indicates that phased deployment approaches achieve 55% higher success rates compared to aggressive rollout strategies [11]. Key considerations include:

Stakeholder engagement frameworks show 82% effectiveness in addressing public concerns. Technology validation protocols demonstrate 91% accuracy in safety assessments [12]. Market readiness indicators suggest optimal implementation windows varying by region and use case.

Table 2: Smart City Integration Effects on Urban Transportation [11, 12]

Impact Category	Small Cities (%)	Medium Cities (%)	Large Metros (%)	Megacities (%)
Congestion Reduction	15	20	25	30
Parking Space Savings	20	25	30	35
Emission Reduction	18	23	28	32
Safety Improvement	25	30	35	40
Infrastructure Usage	22	28	33	38
Public Transport Impact	15	20	25	30

7. Conclusion

The evolution of human-in-the-loop ADAS represents a critical milestone in the development of autonomous vehicle technologies, fundamentally reshaping the relationship between drivers and their vehicles. Through the integration of sophisticated sensor fusion, adaptive control systems, and machine learning algorithms, modern vehicles are achieving unprecedented levels of safety and reliability while maintaining essential human oversight. The successful implementation of teleoperation frameworks and remote assistance capabilities further demonstrates the industry's commitment to ensuring robust fallback options and building user trust. As regulatory frameworks continue to evolve and technology advances, the focus on shared control paradigms emerges as a key factor in fostering public acceptance and confidence in autonomous systems. This balanced approach, combining the strengths of human judgment with artificial intelligence, paves the way for a future where autonomous vehicles seamlessly integrate into our transportation infrastructure while maintaining the crucial element of human agency. The industry's ongoing dedication to developing trust-building mechanisms through transparent and reliable systems suggests a promising trajectory toward widespread adoption of autonomous vehicle technologies, ultimately leading to safer and more efficient transportation systems for society as a whole.

References:

[1] Kaspar Raats et al., "Trusting autonomous vehicles: An interdisciplinary approach," Transportation Research Interdisciplinary Perspectives, vol. 7, Sep. 2020. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S2590198220301123

[2] Prof. Mr Abhilash CD et al., "Understanding ADAS Systems and Its Future Developments," International Journal of Novel Research and Development, vol. 9, no. 07, Jul. 2024. [Online]. Available: https://www.ijnrd.org/papers/IJNRD2407285.pdf

[3] Kyusang Yoon et al., "Adaptive Decentralized Sensor Fusion for Autonomous Vehicle Estimating the Position of Surrounding Vehicles," IEEE Access, 30 August 2023. [Online]. Available: https://scholarworks.bwise.kr/hanyang/bitstream/2021.sw.hanyang/196248/1/Adaptive%20Decentralized%20Sensor%20Fusion%20for%20Autonomous%20Vehicle%20Estimating%20the%20Position%20of%20Surrounding%20Vehicles.pdf

[4] Hussein Bilal et al., "Collaborative human and computer controls of smart machines – A proposed hybrid control," Journal of Industrial Information Integration, vol. 42, Nov. 2024. [Online]. Available: https://www.sciencedirect.com/science/article/abs/pii/S2452414X24001274

[5] Tomasz Neumann, "Analysis of Advanced Driver-Assistance Systems for Safe and Comfortable Driving of Motor Vehicles," ResearchGate, vol. 24, no. 19, Sep . 2024. [Online]. Available:

https://www.researchgate.net/publication/384389669_Analysis_of_Advanced_Driver-Assistance_Systems_for_Safe_and_Comfortable_Driving_of_Motor_Vehicles

[6] Jothimani Cs, "Semi Automatic and Autonomous Controlled Vehicles," International Journal of Bio-Science and Bio-Technology, vol. 11, no. 2, Jan. 2018. [Online]. Available: https://www.researchgate.net/publication/337242215_Semi_Automatic_and_Autonomous_Controlled_Vehicles

[7] Snehanjali Kalamkar et al., "Remote Monitoring and Teleoperation of Autonomous Vehicles -- Is Virtual Reality an Option," ResearchGate, April 2023. [Online]. Available: https://www.researchgate.net/publication/370227500_Remote_Monitoring_and_Teleoperation_of_Autonomous_Vehicles_--_Is_Virtual_Reality_an_Option

[8] Hannah Parr et al., "Investigating levels of remote operation in high-level on-road autonomous vehicles using operator sequence diagrams," Cognition Technology and Work, vol. 26, no. 2, April 2024. [Online]. Available: https://www.researchgate.net/publication/380031454_Investigating_levels_of_remote_operation_in_high-level_on-road_autonomous_vehicles_using_operator_sequence_diagrams

[9] Chandrayee Basu and Mukesh Singhal, "Trust Dynamics in Human Autonomous Vehicle Interaction:A Review of Trust Models," The Association for the Advancement of Artificial Intelligence, 2016. [Online]. Available: https://cdn.aaai.org/ocs/12746/12746-56116-1-PB.pdf

[10] Keng L. Siau et al., "Building Trust in Artificial Intelligence, Machine Learning and Robotics," ResearchGate, March 2018. [Online]. Available: https://www.researchgate.net/publication/324006061_Building_Trust_in_Artificial_Intelligence_Machine_Learning_and_Robotics

[11] Future Agenda Limited, "The future of autonomous vehicles: Global Insights gained from Multiple Expert Discussions," Connected Automated Driving EU. [Online]. Available: https://www.connectedautomateddriving.eu/wp-content/uploads/2023/06/Future-Agenda-open-foresight-The-future-of-autonomous-

vehicles-Global-Insights-gained-from-Multiple-Expert-Discussions_01-04-2020_Future-Agenda-Limited.pdf

[12] O. Kevin Vincent, "A Regulatory Framework for Autonomous Vehicle Deployment and Safety," Secureenergy, May 2021. [Online]. Available: https://secureenergy.org/wp-content/uploads/2021/05/Kevin-Vincent-Regulatory-Framework.pdf

Citation: Vraj Mukeshbhai Patel. Trust-Building Through Shared Control: Human-in-the-Loop ADAS. International Journal of Computer Engineering and Technology (IJCET), 16(1), 2025, 3316-3330.

Abstract Link: https://iaeme.com/Home/article_id/IJCET_16_01_231

Article Link:
https://iaeme.com/MasterAdmin/Journal_uploads/IJCET/VOLUME_16_ISSUE_1/IJCET_16_01_231.pdf

editor@iaeme.com